

Stand-in double stacker truck 2.0 ton

BT STAXIO

S-series

SSI200D

LI-ION

Lithium-Ion Energy System



Stand-in double stacker truck

Specification					SSI200D
Identification	1.1	Manufacturer			Toyota
	1.2	Model			SSI200D
	1.3	Drive			Electric
	1.4	Operator type			Stand-in
	1.5	Load capacity/rated load	Q	kg	1000+1000
	1.6	Load center	c	mm	600
	1.8	Load distance (support arms raised/lowered)	x	mm	979/1010
	1.9	Wheelbase (support arms raised/lowered)	y	mm	1835/1866
	Weight	2.1	Service weight without battery		kg
2.2		Axle load, with load, drive/castor/support arm wheel		kg	627/611/2011
2.3		Axle load, without load, drive/castor/support arm wheel		kg	485/400/365
Wheels	3.1	Drive/castor/fork wheel			Polyurethane*
	3.2	Wheel size, front		mm	ø250x92
	3.3	Wheel size, rear		mm	ø85x74
	3.4	Additional wheel size		mm	ø140x86
	3.5	Wheels, number front/rear (X = driven wheels)			2(1X) / 4
	3.6	Track width, front	b ₁₀	mm	460
	3.7	Track width, rear	b ₁₁	mm	390
Dimensions	4.2	Height, mast lowered	h ₁	mm	1410*
	4.3	Free lift	h ₂	mm	172*
	4.4	Lift	h ₃	mm	1660*
		Lift height	h ₂₃	mm	1750*
	4.5	Height, mast extended	h ₄	mm	2268*
	4.6	Initial Lift	h ₅	mm	120
	4.7	Height of overhead guard (cabin)	h ₆	mm	2350
	4.8	Stand height	h ₇	mm	262
	4.15	Height, fork lowered	h ₁₃	mm	90
	4.18	Overall chassis height	h ₁₅	mm	TBA
	4.19	Overall length	l ₁	mm	2222
	4.20	Length to face of forks	l ₂	mm	1022
	4.21	Overall width	b ₁	mm	790
	4.22	Fork dimensions	s/e/l	mm	70/180/1200
	4.25	Width over forks	b ₅	mm	570
	4.32	Ground clearance, center of wheelbase	m ₁	mm	19,5
	4.33	Aisle width for pallets 1000x1200 crossways	A _{st}	mm	2851
4.34	Aisle width for pallets 800x1200 crossways	A _{st}	mm	2694	
4.35	Turning radius	W _a	mm	2051	
Performance data	5.1	Travel speed, with/without load		km/h	8/11,5
	5.2	Lift speed, with/without load		m/s	0,26/0,43
	5.3	Lowering speed, with/without load		m/s	0,45/0,47
	5.8	Max. gradeability, with/without load ¹⁾		%	8/12
	5.9	Acceleration time (over 10 m)		s	5,5
	5.10	Service brake			Electromagnetic
Electric motor	6.1	Drive motor rating S2 60 min		kW	2,8
	6.2	Lift motor rating (S3 15%) / for 200DN (S3 8.5 at 150 bar)		kW	3
	6.4	Battery voltage/nominal capacity K _s		V/Ah	24/210,300,420
	6.5	Battery weight		kg	29, 44, 58
	6.6	Energy consumption according to EN16796		kWh/h	0,62
	Others	8.1	Type of drive control		
8.4		Sound level at the driver's ear according to EN12053		dB (A)	67

* Further alternatives are available and will produce other values. Data is based on configuration with Duplex Tele mast, 1750 mm (h23).

All data are based on table configuration. Other configurations may give other values.

Truck performance and dimensions are nominal and subject to tolerances.

Toyota Material Handling Manufacturing Sweden AB products and specifications are subject to change without notice.

Truck features:

- Fingertip controls
- Adjustable sit/stand chair
- 180° or 360° steering mode
- Driver detection system
- Multifunction colour touchscreen
- Carefree Li-Ion energy solution
- Automatic speed reduction in curves
- Blue LED warning light option
- Cold store option
- Automatic deceleration
- Automatic parking brake
- Clear view mast
- Electronic braking system
- Electronic regenerative brakes (motor)
- Electronic speed control

